



SPECIFICATIONS

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 2-way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 6" round shower head and 8" shower arm
- Round tub spout with fluid quick connection
- Requires pressure balancing valve with shut off F1012B or F1012B-PEX or F1012B-PEX-W or
- Requires pressure balancing valve with sharing F1012B-SHARE or F1012B-SHARE-PEX or F1012B-SHARE-PEX-W
- Valve package and trim package are sold separately

Finish

- CP (Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Citi Series **Tub and Shower Trim Kit** Model: F242002T

Customer Service: 1-800-460-7019

www.fluidfaucets.com

FP6016008

FP6057034

Includes: F1001T Sleeve Tube and Cap Diverter Sleeve Tube FP801013 FP6024041 Citi Handle FP605652 Diverter Handle FP6001142-2PB Round Cover Plate 6" Shower Head FP6000350 8" Shower Arm



Round Tub Spout









