

SPECIFICATIONS

Customer Service: 1-800-460-7019
www.fluidfaucets.com

Specifications

- Heavy forged brass construction for durability and reliability
- German made brass thermostatic cartridge ensures anti-scald operation, temperature control and a life long trouble free service
- German made brass body ceramic 3 way diverter cartridge allows the volume control
- Temperature button stops the handle rotation at 100°F/38°C for anti-scald protection. If water above 100°F/38°C is desired, press the button and turn the handle counterclockwise.
- Max-temperature limit stop for added safety
- Integral stop valves for an easy maintenance
- Dual inlet and outlet ports – 1/2" CxC soldering & 1/2" NPT thread
- Adjustable installation depth from 2-11/16"(68mm) to 3-5/16" (84mm)
- Mud guard is provided to protect trim finish.
- A wide selection of trims to compliment are sold separately

Flow Rate

- 13.5 gpm @ 60 psig

Finish

- Brass

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

fluid Thermostatic Valve 3 Way Diverter Model: F5003B

