

GEBERIT SIGMA50 ACTUATORS For Sigma Concealed Tanks, 2x6 and 2x4 Installations

SPECIFICATIONS

Actuators for concealed tank and carrier system. Actuator flush plates and push buttons shall be glass, zinc die-cast, or molded plastic and plated to guard against scratches. All components shall be compliant with applicable codes and product standards.

FEATURES

- Designed to maintain appearance push after push
- Moving parts are accessible behind actuator flush plate
- Made of glass, molded plastic or zinc die cast
- Available in a variety of unique combinations of finish/color
- Incorporates water saving possibilities when used with Geberit dual-flush tanks 1.6 GPF (6 LPF) and 0.8 GPF (3 LPF) or 1.28 GPF (4.8 LPF) and 0.8 GPF (3 LPF)
- Includes mounting frame and hardware

WARRANTY


One-year limited warranty

ç. Dual-Flush Actuators, Sigma 2x6 and 2x4 Installation

Style	Material	Finish	Model No.
Sigma50	Die Cast	Customizable	115.788.00.2
		White	115.788.11.2
		Black	115.788.DW.2
NEW! May 2019		Smoked Glass	115.788.SD.2
		Umber Glass	115.788.SQ.2
		Sand Glass	115.788.TG.2
		Mustang Slate	115.788.JM.2
		Bright Chrome	115.788.21.2
		Brushed Chrome	115.788.GH.2

DIMENSIONS Sigma50 Dual-Flush





Products marked with 🛃 comply with the American Disabilities Act (ADA) when installed per the requirements of the latest ADA Accessibility Guidelines (ADAAG) and/or ICC/ANSI A117.1.



ARCHITECT/ENGINEER APPROVAL

Date:

Variations Specified:

Customer/Wholesaler:

Contractor:

Architect:

KNOW HOV **INSTALLED**

Geberit 2100 S. Clearwater Drive Des Plaines, IL 60018 USA

P 847-803-7777 F 847-849-1845

www.geberit.us

Job Name: Quantity: Model Specified: