IWS 3S + DryDock™ 12 in stock

IWS-3-S-DD-12-S-BA



IWS-3-S-DD-12-S-GT



IWS-3-S-DD-12-S-WH



IWS-3-S-DD-12-S-GR



Specifications


Single bowl Users: 1 Culinary Tools included: Six (7 pcs) Outside dimensions: 45 1/2" x 19 1/2" x 2 1/16" Counter top cutout: 44 1/2" x 18" Minimum cabinet size: 48" or 120cm Minimum clearance required for DryDock™ below counter top: 2" DryDock[™] location: Drain side (S)


Culinary Tools included

- (1) Upper Tier Cutting Board 12 1/4" x 18"
- (1) Upper Tier Drying Rack 12 1/4" x 18"
- (1) 11" Colander
- (1) 11" Mixing Bowl with lid
- (1) Lower Tier Platform for Colander, Mixing Bowl 12 1/4" x 17"
- (1) Lower Tier Drying Rack 12 1/4" x 17"
- (1) 12" Upper Deck

Basin construction

16GA 316L stainless steel indoor/outdoor Angel finish Two tier design Star™ groove pattern Reversible side drain Drain cover included Limited Lifetime Warranty Made in the USA ASME A112.19.3/CSA B45.4 certified





US Suggested maximum inside corner radius of counter top cutout 3/8" Center Tap hole diameters 2" behind cutout T. Galley Dack Switch 1 3/8" min hole diameter (1 1/2" min hole diameter for fast water jet cut) 1. Galley Deck Switch 1 3/8" min hole diameter or Galley Automatic Strainer Basket knob 1" min and 1 3/8" max hole diameter 2. Galley Hot and Cold Water Dispenser 1" 3/8" min hole diameter (1 1/2" min hole diameter for fast water jet cut) or Galley Soap Dispenser 1" min to 1 3/8" max hole diameter 3. Galley Soap Dispenser "Galley Hot and Cold Water dispenser requires a minimum 8" clearance to center if installed to the right of the Galley Tap