

R4RD2L, R4SD2L

4.5" Volta - Downlight Trimless

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

FEATURES

- 2" lens regress for superior glare control
- Field selectable light engine height for cut-off angle adjustment (30° - 34°) and accessory use
- Integral patterned tempered trim lens included standard
- Compatible with wide range of accessories
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input: Universal 120 - 277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-5%
0-10V: 100%-0%
Lutron Hi-Lume 1% Ecosystem Fade-to-Black option

Light Source: High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly. Safety cabling standard.
Ceiling cut out (Round): Ø 5 1/8"
Ceiling cut out (Square): 5 1/8" x 5 1/8"
Accommodates 1/2" - 1 1/2" ceiling thickness

Finish: Electrostatically powder coated White, Black. Enamel coated Haze. Plated and brushed Bronze

Standards: ETL & cETL Wet location Listed, Energy Star® 2.0, Title 24 JA8-2016 Compliant

TRIMS (ORDER HOUSING SEPARATELY)

Model	Beam Angle	Reference Output*			Color Temp	CRI	Finishes	Reflector/Trim
		Lumens	CBCP	Lumen/Watt				
	R4RD2L <i>Round</i>	S 15°	1405	11420	65	827 2700K 85 927 2700K 90 830 3000K 85 930 3000K 90 835 3500K 85 840 4000K 85	BK Black HZ Haze WT White CB Bronze	
		N 25°	3145	9615	94			
		F 45°	3025	5005	90			
	R4SD2L <i>Square</i>	W 60°	2895	3125	85			
		S 15°	1440	11985	66			
		N 25°	3350	9820	99			
	F 45°	3200	4935	95				
	W 60°	3060	3055	90				

*Reference output shows **830**(85CRI 3000K) trim with **36** housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM					
	827	927	830	930	835	840
HOUSING 36	0.95	0.81	1.00	0.86	1.05	1.07
HOUSING 25	0.66	0.56	0.69	0.59	0.73	0.74
HOUSING 15	0.43	0.37	0.45	0.39	0.48	0.49

R4_D2L-_____-_____

Example: **R4RD2L-S827-WT**

Please see next page for housing units(required)

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

R4RD2L, R4SD2L

4.5" Volta - Downlight Trimless

WAC LIGHTING

Responsible Lighting®

HOUSINGS (REQUIRED)

		Model	Power*	S	N, F, W	Rating	Driver	Emergency Backup	
<i>Round New Construction</i> 	R4RNL <i>Airtight</i>	R4RCL <i>Airtight, Chicago Plenum</i>	15	10W	15W	IC rated	DEFAULT L1	<i>ELV, 0-10V</i> <i>Lutron</i> <i>Hi-Lume 1%</i>	EM
	R4RCL <i>Airtight, Chicago Plenum</i>		25	15W	23W	IC rated			
<i>Square New Construction</i> 	R4SNL <i>Airtight,</i>	R4SCL <i>Airtight, Chicago Plenum</i>	15	10W	15W	IC rated	DEFAULT L1	<i>ELV, 0-10V</i> <i>Lutron</i> <i>Hi-Lume 1%</i>	EM
	R4SCL <i>Airtight, Chicago Plenum</i>		25	15W	23W	IC rated			
			36	22W	34W	Non-IC			

*Power consumption depends on beam angle of the trim.

Field Replaceable Driver


D-R4N-15	Driver for 15W New Construction Hsg
D-R4N-25	Driver for 23W New Construction Hsg
D-R4N-36	Driver for 34W New Construction Hsg

R4 _____ - _____

Example: **R4RNL-15** or **R4RNL-15EM** (with Emergency backup battery)

Trimless housings come included with die-cast spackle frame.

FIELD CHANGEABLE GLARE CONTROL AND OPTIC SYSTEM



Accessory holder	
LENS-73-HLD	Required to hold lens and glare control accessories
Glare control accessories	
LENS-73-HCL	Honeycomb Louver
LENS-73-CRL	Cross Louver

Lens	
LENS-73-AMB	Amber lens
LENS-73-RED	Red lens
LENS-73-FR	Frosted lens
LENS-73-SPR	Spread lens
LENS-73-BEL	Beam Elongating

Interchangeable Reflector	
REF-R4-N	Narrow Flood beam reflector
REF-R4-F	Flood beam reflector
REF-R4-W	Wide beam reflector

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760