

Features

- HydroRail-R arch shower column designed for new installations or retrofit applications to replace an existing shower arm
- 8" Awaken® rainhead with a full coverage spray and an adjustable ball joint for precise spray adjustment
- Shift+ round multifunction handshower offers full coverage and targeted massage spray options
- Full coverage produces an encompassing spray ideal for everyday use
- Targeted spray is a focused stream for targeting sore muscles or use as a utility spray
- MasterClean™ sprayface features an easy-to-clean surface that withstands mineral buildup
- 2.5 gpm (9.5 lpm) maximum flow rate at 45 psi (3.1 bar)
- Slidebar bracket allows you to adjust the height and angle of the handshower
- Diverter at base of column makes for easy toggling between handshower and showerhead
- Handshower contains flow-regulating check valve for backflow prevention

Material

- Durable material construction
- KOHLER finishes resist corrosion and tarnishing

Installation

- Shower-only wall-mount installation
- Installs in less than 60 minutes without changes to in-wall plumbing (subject to condition of existing installation)
- May require additional service parts based on installation type (see installation guide for details)

Recommended Products/Accessories

K-23723 Faucet cleaner


Optional Products/Accessories

K-9660 Vacuum Breaker
1194302

Included Components

Additional Components:

45211
45415-A
76464
9514



Codes/Standards

ASME A112.18.1/CSA B125.1
DOE - Energy Policy Act 1992


KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	BN	Vibrant® Brushed Nickel
	BL	Matte Black



Technical Information

All product dimensions are nominal.

Drain included: No

Handshower:

Rated maximum flow: 2.5 gal/min (9.5 l/min)

Pressure: 45 psi (3.1 bar)

Showerhead/Body Spray:

Rated maximum flow: 2.5 gal/min (9.5 l/min)

Pressure: 45 psi (3.1 bar)

Notes

Install this product according to the installation instructions.